

C5255 / C5250  
C5240 / C5235

## Product Specifications



### Main Unit

#### System Type

Color Digital Multifunction Imaging System

#### Functions

Standard: Copy, Print (UFR II), Scan, Send, Store  
Optional: Print (PCL, Adobe® PostScript® 3™), Fax (Up to 4 Lines)

#### Operation Panel

8.4" SVGA Full-Color TFT Screen

#### Memory

Standard: 2GB RAM  
Maximum: 2.5GB RAM

#### Hard Disk Drive

Standard: 160GB  
Maximum: 1TB

#### Mirroring Hard Disk Drive

Optional (160GB, 1TB), Method: RAID1

#### Network Interface Connection

Standard: 1000Base-T/100Base-TX/10Base-T  
Optional: Wireless LAN (IEEE 802.1x via third-party adapter)

#### Other Interface

Standard: USB 2.0 (Host) x 2, USB 2.0 (Device)  
Optional: Device Port [USB 2.0 (Host) x 2], Serial Interface, Copy Control Interface

#### Copy/Print Speed (BW/Color)

Letter:	C5255:	Up to 55/51 ppm
	C5250:	Up to 50/45 ppm
	C5240:	Up to 40/35 ppm
	C5235:	Up to 35/30 ppm
Legal/11" x 17":	C5255:	Up to 28/26 ppm
	C5250:	Up to 28/26 ppm
	C5240:	Up to 20/18 ppm
	C5235:	Up to 20/18 ppm

#### First-Copy-Out Time (Letter)

C5255/C5250: BW: 3.9 Seconds, Color: 6.0 Seconds  
C5240/C5235: BW: 5.4 Seconds, Color: 8.1 Seconds

#### Paper Sources (20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet Stack Bypass  
Optional: Dual 550 Sheet Paper Cassettes, 2,700-sheet Paper Deck  
Maximum: 5,000 Sheets

#### Output Paper Capacity (20 lb. Bond)

Standard: 250 Sheets (Inner Tray)  
Maximum: 3,250 Sheets (w/Staple Finisher or Booklet Finisher)

#### Output Paper Sizes

Cassettes: 12" x 18",\* 11" x 17",\* Legal, Letter, Letter-R, Statement-R, Executive, Custom Size (5-1/2" x 7-1/8" to 12" x 18")  
Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18")  
Paper Deck: Letter  
Other: Envelope Feeder Attachment (COM10 No.10)  
Options: Monarch, DL, ISO-C5)\*\*  
Tab Feeding Attachment Kit\*\*

#### Acceptable Paper Weights

Cassettes: 14 lb. Bond to 80 lb. Cover (52 to 220g/m<sup>2</sup>)  
Bypass: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)

#### Duplexing

Paper Size: Standard Automatic Trayless Duplexing (Executive to 12" x 18")  
Paper Weights: 14 lb. Bond to 80 lb. Cover (52 to 220g/m<sup>2</sup>)

#### Special Media Support

Thin, Plain 1 [17 lb. Bond to 21 lb. Bond (64g/m<sup>2</sup> to 81g/m<sup>2</sup>)], Plain 2 [22 lb. Bond to 28 lb. Bond (82g/m<sup>2</sup> to 105g/m<sup>2</sup>)], Recycled, Color, Pre-Punched, Bond, Heavy 1 [29 lb. Bond to 60 lb. Cover (106g/m<sup>2</sup> to 163g/m<sup>2</sup>)], Heavy 2 [61 lb. Cover to 80 lb. Cover (164g/m<sup>2</sup> to 220g/m<sup>2</sup>)], Heavy 3 [82 lb. Cover to 140 lb. Index (221g/m<sup>2</sup> to 256g/m<sup>2</sup>)], Tracing, Coated, Labels, Transparency, Tab, Letterhead, and Envelopes

#### Warm-up Time

C5255/C5250: From Power On: 31 Seconds, From Sleep: 18 Seconds  
Quick Startup Mode: 7 Seconds\*\*\*  
C5240/C5235: From Power On: 31 Seconds, From Sleep: 15 Seconds  
Quick Startup Mode: 7 Seconds\*\*\*

#### Power Requirements/Plug

C5255/C5250: 120V AC, 60Hz, 20A/NEMA 5-20P  
C5240/C5235: 120V AC, 60Hz, 15A/NEMA 5-15P

#### Power Consumption

Maximum: C5255/C5250: 1.8kW  
C5240/C5235: 1.5kW  
Sleep Mode: 0.8W

#### Dimensions (H x W x D)

C5255/C5250: 37-3/8" x 24-3/8" x 28-1/8"  
(950mm x 620mm x 715mm)  
C5240/C5235: 36-5/8" x 24-3/8" x 28"  
(931mm x 620mm x 712mm)

#### Installation Space (W x D)

C5255/C5250: 33-1/2" x 28-1/8" (850mm x 715mm)  
C5240/C5235: 33-1/2" x 28" (850mm x 712mm)

#### Weight

C5255/C5250: Approx. 346 lb. (157kg)<sup>†</sup>  
C5240/C5235: Approx. 333 lb. (151kg)<sup>†</sup>

#### Toner (Estimated Yield @ 5% Coverage)

C5255/C5250: Black: 44,000 Images, Color (C,M,Y): 38,000 Images  
C5240/C5235: Black: 36,000 Images, Color (C,M,Y): 27,000 Images

## Main Unit (continued)

### Image Reader Unit

#### Scan Resolution

Up to 600 x 600 dpi

#### Acceptable Originals (Glass)

Sheet, Book, 3-Dimensional objects [up to 4.4 lb. (2kg)]

#### Maximum Original Size

Up to 11" x 17"

### Document Feeder

#### Scan Method

**C5255/C5250:** Single-Pass Duplexing, Automatic Document Feeder

**C5240/C5235:** Duplex Automatic Document Feeder

#### Acceptable Originals

Paper Sizes: 11" x 17", Legal, Letter, Letter-R, Statement, or Statement-R

Paper Weights: 1-sided scanning: 11 lb. Bond to 58 lb. Cover (42 to 157g/m<sup>2</sup>)

2-sided scanning: 13 lb. Bond to 58 lb. Cover (50 to 157g/m<sup>2</sup>)

#### Scan Speed (BW/Color; Letter)

**C5255/C5250:** Simplex: Up to 75/75 ipm (300 dpi)/ Up to 75/51 ipm (600 dpi)  
Duplex: Up to 120/120 ipm (300 dpi)/ Up to 75/51 ipm (600 dpi)

**C5240/C5235:** Simplex: Up to 51/51 ipm (300 dpi)/ Up to 46/46 ipm (600 dpi)  
Duplex: Up to 19.6/19.6 ipm (300 dpi)/ Up to 17.5/17.5 ipm (600 dpi)

#### Paper Capacity (20 lb. Bond)

**C5255/C5250:** 150 Sheets

**C5240/C5235:** 100 Sheets

### Copy Specifications

#### Multiple Copies

1 to 999

#### Copy Exposure

Automatic or Manual (9 Levels)

#### Magnification

25% - 400% (1% Increments)

#### Preset Reductions

25%, 50%, 64%, 73%, 78%

#### Preset Enlargements

121%, 129%, 200%, 400%

#### Basic Copy Features

Preset R/E Ratios by Area, Finishing, Two-Sided, Exposure Adjustment, Original Type Selection, Interrupt Mode, Sample Set, Setting Confirmation/Cancel, Standard Keys, Reset, Guide Display, Job Duration Display, Reserved Copying

#### Special Copy Features

Two-page Separation, Cover/Sheet Insertion, Booklet, Transparency Interleaving, Shift, Margin, Frame Erase, Image Combination, Different Size Original, Job Build, Job Done Notice, Scan Image Check, Mode Memory, Recall, Negative/Positive Inversion, Image Repeat, Mirror Image, Sharpness, Tab Paper Creation, Form Composition, Secure Watermark, Page Numbering, Copy Set Numbering, Watermark and Date, Job Block Combination, Store in User Inbox

### Print Specifications

#### Processor

Canon Dual Custom Processor (Shared)

#### Memory

Standard: 2GB RAM

Maximum: 2.5GB RAM

#### Hard Disk Drive

Standard: 160GB

Maximum: 1TB

#### Engine Resolution

1200 x 1200 dpi

#### PDL Support

Standard: UFR II

Optional: PCL 5c, PCL 6, Adobe PS 3

#### Print Driver Supported OS

UFR II, PCL 5c/6, Adobe PS 3:  
Windows® (XP/Windows Vista®/7), Windows Server (2003/2008/2008 R2/SBS 2011/2012), Windows Terminal Servers (Server 2003/Server 2008/Server 2008 R2/2012), Microsoft® Clustering Server (Server 2003/Server 2003 R2/Server 2008/Server 2008 R2), Citrix (Presentation Server 4.5, Xen App 5.0/6.0/6.5, Xen Desktop 4.0/5.0/5.5), Macintosh® (OS X 10.5.8 or later, UFR II and PS 3 only), VMware, SAP (PS and PCL Only)

#### Direct Print Support

Standard: TIFF, JPEG

Optional: PDF, XPS<sup>+</sup>, EPS<sup>++</sup>

#### Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Black and White Printing, Objective, Color/Black-and-White Auto Detect, Toner Reduction, Poster Printing

### Scan Specifications

#### Network TWAIN Scan

Standard

#### Network Scan Utility

Color Network ScanGear

### Universal Send Specifications

#### Sending Method

E-Mail, I-Fax, File Server (FTP, SMB, WebDAV), Mail Box, Super G3 Fax (Optional)

#### Color Mode

Auto Color Select (Color, Gray), Auto Color Select (Color, Black), Full Color, Grayscale, BW

#### Scan Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

#### Address Book Capacity

Max. 1,800 Destinations (Incl. 200 One-Touch Buttons)

#### Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP), WebDAV

E-mail/I-Fax: SMTP, POP3, I-FAX (Simple, Full)

#### File Format

Standard: TIFF, JPEG, PDF, PDF (Compact), PDF (Apply Policy), PDF (Optimize for Web), PDF/XPS (OCR), PDF/A-1b, XPS, XPS (Compact), OOXML (OCR) (.pptx and .docx)

Optional: PDF (Trace & Smooth), PDF (Encrypted), PDF/XPS (Digital Signature), PDF (Reader Extensions)

#### I-Fax Data Format

Color: .tfx (JPEG)

BW: .tif (MH, MR, MMR)

#### Universal Send Features

Two-Sided Original, Different-size Originals, Original Type Selection, Book to Two Pages, Density Adjustment, Sharpness, Document Name, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, Sender's Name (TTI), E-Mail Priority

### Fax Specifications

#### Maximum Number of Connection Lines

4

#### Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

#### Compression Method

MH, MR, MMR, JBIG

#### Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

#### Sending/Recording Size

Statement to 11" x 17"

#### Fax Features

Job Forwarding, Different-size Originals, Adjusting Overall Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Selecting the Telephone Line (when sending fax), Delayed Send, Preview, Finished Stamp, Job Done Notice, Original Type Selection, Two-sided Original, Book to Two Pages

## Main Unit (continued)

### Store Specifications

#### Mail Box (Number supported)

100 User Inboxes, 1 Memory RX Inbox,  
50 Confidential Fax Inboxes  
6,000 Maximum Pages Stored

#### Advanced Box

Available Approx. 15GB (Standard HDD)  
Disk Space: Approx. 629GB (ITB HDD)  
Communication Protocol: SMB or WebDAV  
Supported Client PC: Windows® (Windows 2000/XP/Windows Vista®)  
Concurrent Connections (Max.): SMB: 32, WebDAV: 12 (Active Sessions)  
Advanced Box Features: Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

#### Memory Media

Standard: USB Memory  
Optional: SD, SDHC, CompactFlash, Memory Stick, Microdrive

### Security Specifications

#### Standard

Department ID Management, Single Sign On-H, Access Management System (Device and Function Level Log-in), Secured Print, Trusted Platform Module, User Access Control of Advanced Box, Mail Box Password Protection, IPV6, Restricting Features (Restricting the Send Function, Restricting New Addresses on Address Book), SSL Encrypted Communication, SNMPv1/v3, MAC/IP Address Port Filtering, SMTP Authentication, POP Authentication before SMTP, HDD Erase (Up to 3x), HDD Initialize (Up to 9x), HDD Lock, IPsec, Adobe LiveCycle Rights Management ES2.5 Integration

#### Optional

Removable HDD, HDD Encryption, HDD Mirroring, Encrypted Secure Print, Encrypted PDF, Document Scan Lock, Secure Watermark, IEEE 2600.1 Common Criteria Certification\*

### Environmental Information

#### ENERGY STAR® Qualified

#### RoHS Compliant

#### Ecomark

#### Blue Angel

#### WEEE Directive

## Optional Accessories

### Paper Supply Options

#### Cassette Feeding Unit-AD2

Paper Capacity: 550 Sheets x 2 Cassettes [20 lb. Bond (80g/m<sup>2</sup>)]  
Acceptable Paper Weight: 14 lb. Bond to 80 lb. Cover (52 to 220g/m<sup>2</sup>)  
Acceptable Paper Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive, and Custom Size [5-1/2" x 7-1/8" to 12" x 18" (139.7mm x 182mm to 304.8mm x 457.2mm)]

Power Source/ Maximum Power Consumption: From the Main Unit/Approximately 30W  
Dimensions (H x W x D): 9-7/8" x 24-3/8" x 27-5/8" (251mm x 620mm x 700mm)  
Weight: Approximately 61.7 lb. (28kg)

#### Paper Deck Unit-B2

Paper Capacity: 2,700 sheets [20 lb. Bond (80g/m<sup>2</sup>)]  
Number of Drawers: 1  
Acceptable Paper Weight: 14 lb. Bond to 60 lb. Cover (52 to 163g/m<sup>2</sup>)  
Acceptable Paper Size: Letter

Power Source/ Maximum Power Consumption: From Main Unit/Approximately 45W  
Dimensions (H x W x D): 18-5/8" x 14-5/8" x 23-3/4" (473mm x 372mm x 603mm)  
Weight: Approximately 81.6 lb. (37kg)

#### Envelope Feeder Attachment-D1\*\*

Paper Capacity: 50 Sheets (or 30mm in height)  
Acceptable Paper Size: COM10 No.10, Monarch, DL, ISO-C5  
Feeding Speed: 10 cpm  
Dimensions (H x W x D): 3-1/4" x 17-1/4" x 12-1/8" (81mm x 439mm x 307mm)  
Weight: Approximately 2.6 lb. (1.2kg)

### Output Options

#### Inner 2-way Tray-F1\*

Number of Trays: 2  
Total Output Capacity: **Top Tray:** 250 Sheets (20 lb. Bond) **Lower Tray:** 100 Sheets (20 lb. Bond)  
Acceptable Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)  
Acceptable Paper Size: 12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-9/16" to 12-5/8" x 18" (99mm x 139.7mm to 320mm x 457.2mm)], and Envelopes  
Dimensions (H x W x D): 3" x 16-3/4" x 16" (76mm x 427mm x 407mm)  
Weight: Approximately 1.3 lb. (574g)

#### Inner Finisher-E1\*

Number of Trays: Up to 2 Trays (With Inner Finisher Additional Tray-A1)  
Total Output Capacity: **Without Inner Finisher Additional Tray-A1:** 500 Sheets **With Inner Finisher Additional Tray-A1**  
**Top Tray:** 100 Sheets (Letter) **Lower Tray:** 200 Sheets (Letter)  
Acceptable Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)  
Acceptable Paper Size: 12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom size (3-7/8" x 5-9/16" to 12-5/8" x 18"), and Envelopes  
Staple Positions: **Corner Stapling** (11" x 17", Legal, Letter, Letter-R) **Double Stapling** (11" x 17", Legal, Letter, Letter-R)  
Maximum Stapling Capacity: **Letter and Executive:** 50 Sheets (14 to 21 lb. Bond) 30 Sheets (22 to 28 lb. Bond) 2 Sheets (29 lb. Bond to 140 lb. Index) **11" x 17", Legal and Letter-R:** 30 Sheets (14 to 21 lb. Bond) 20 Sheets (22 to 28 lb. Bond) 2 Sheets (28 lb. Bond to 140 lb. Index)

Paper Capacity of Staple Mode: **Top Tray:** 3/8" in height **Lower Tray:** 30 Sets (or 2-1/2" in height)  
Type of Staple: Staple-J1 (5,000 x 3)  
Power Source/ Maximum Power Consumption: From the Main Unit/Approximately 40W  
Dimensions (H x W x D): 9-1/4" x 34-1/8" x 21-1/4" (234mm x 865mm x 540mm (When the Auxiliary Tray is extended))  
Weight: Approximately 28.7 lb. (13kg)

#### Staple Finisher-J1\*

Number of Trays: 2  
Total Output Capacity: 3,000 Sheets (Letter, Statement-R, Executive) **Top Tray:** 1,300 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R) **Lower Tray:** 1,700 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)  
Acceptable Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)  
Acceptable Paper Type: Thin, Plain, Recycled, Color, Pre-Punched, Bond, Heavy, Tracing, Letterhead, Coated, Labels, Transparency, and Envelopes  
Acceptable Paper Size: 12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-9/16" to 12-5/8" x 18" (99 x 139.7mm to 320mm x 457.2mm)], and Envelopes  
Staple Positions: **Corner Stapling:** (11" x 17", Legal, Letter, Letter-R, Executive) **Double Stapling:** (11" x 17", Legal, Letter, Letter-R, Executive)

**Optional Accessories** (continued)

**Output Options** (continued)

**Staple Finisher-J1\*** (continued)

Maximum **Letter and Executive:**  
Stapling 50 Sheets (14 to 21 lb. Bond)  
Capacity: 30 Sheets (22 to 28 lb. Bond)  
2 Sheets (29 lb. Bond to 140 lb. Index)  
11" x 17", **Legal and Letter-R:**  
30 Sheets (14 to 21 lb. Bond)  
20 Sheets (22 to 28 lb. Bond)  
2 Sheets (29 lb. Bond to 140 lb. Index)

Paper **Top Tray:**  
Capacity of 1,300 Sheets/30 Sets (Letter, Executive),  
Staple Mode: 650 Sheets/30 Sets (11" x 17", Legal, Letter-R)

**Lower Tray:**  
1,700 Sheets/30 Sets (Letter, Executive),  
650 Sheets/30 Sets (11" x 17", Legal, Letter-R)

Type of Staple: Staple-J1 (5,000 x 3)

Power Source/  
Maximum Power

Consumption: From the Main Unit/Approximately 100W

Dimensions 43-1/4" x 26-5/8" x 25-1/2"  
(H x W x D): [1,097mm x 677mm x 646mm  
(When the Auxiliary Tray is extended)]

Weight: Approximately 101 lb. (46kg)

**Booklet Finisher-J1\***

Number of  
Trays: 2

Total Output  
Capacity: 3,000 sheets (Letter, Statement-R, Executive)

**Top Tray:** 1,300 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)

**Lower Tray:** 1,700 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)

Acceptable

Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)

Acceptable  
Paper Type: Plain, Heavy, Color, Recycled, Pre-Punched, Transparency, Tracing, Labels, Bond, Transparency, Envelopes

Acceptable  
Paper Size: 12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-9/16" to 12-5/8" x 18" (99 x 139.7mm to 320mm x 457.2mm)], and Envelopes

Staple  
Positions: **Corner/Double Stapling:** 11" x 17", Legal, Letter, Letter-R, Executive  
**Saddle-Stitch:** 11" x 17", Legal, Letter-R

**Booklet Finisher-J1\*** (continued)

Maximum **Letter and Executive:**  
Stapling 50 Sheets (14 to 22 lb. Bond)  
Capacity: 30 Sheets (22 to 28 lb. Bond)  
2 Sheets (29 lb. Bond to 140 lb. Index)  
11" x 17", **Legal and Letter-R:**  
30 Sheets (14 to 21 lb. Bond)  
20 Sheets (22 to 28 lb. Bond)  
2 Sheets (29 lb. Bond to 140 lb. Index)

Paper **Top Tray:**  
Capacity of 1,300 Sheets/30 Sets (Letter, Executive),  
Staple Mode: 650 Sheets/30 Sets (11" x 17", Legal, Letter-R)

**Lower Tray:**  
1,700 Sheets/30 Sets (Letter, Executive),  
650 Sheets/30 Sets (11" x 17", Legal, Letter-R)

Maximum  
Saddle-Stitch 16 Sheets (14 to 20 lb. Bond)  
Capacity: 10 Sheets (22 to 28 lb. Bond)

Paper Capacity  
of Saddle-  
Stitch Mode: 25 Booklets (5-sheet Booklets)

Type of Staple: Staple-J1 (5,000 x 3)  
Staple Cartridge-D3 (2,000 x 3)

Power Source/  
Maximum Power

Consumption: From the Main Unit/Approximately 123W

Dimensions 43-1/4" x 31-1/8" x 25-1/2"  
(H x W x D): [1097mm x 789mm x 646mm  
(When the Auxiliary Tray is extended)]

Weight: Approximately 165 lb. (75kg)

**External 2/3 Hole Puncher-B2**

Acceptable  
Punch  
Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256g/m<sup>2</sup>)

Acceptable  
Punch  
Paper Type: Thin, Plain, Heavy, Color, Recycled, Letterhead, Coated

Acceptable  
Punch  
Paper Size: 11" x 17", Legal, Letter, Letter-R

Punch Type: **2 Holes:** (Legal, Letter-R, Executive)  
**3 Holes:** (11" x 17", Letter)

Distance  
Between **2 Holes:** 2-3/4" (70mm)  
Punch Holes: **3 Holes:** 4-1/4" (108mm)

Punch Waste **2 Holes:** 10,000 sheets (21 lb. Bond)  
Tray Capacity: **3 Holes:** 3,000 sheets (21 lb. Bond)

Power Source: From the Main Unit

Dimensions 36x 4-1/4" x 24-1/4"  
(H x W x D): (915mm x 107mm x 615mm)

Weight: Approximately 15.9 lb. (7.2kg)

**Other Optional Accessories**

- Cabinet Type-B1
- Utility Tray-A2
- USB Keyboard
- Universal Keyboard Stand-A1
- Key Switch Unit-A2
- Copy Card Reader-F1
- Convenience Stapler-B1
- Universal Send Advanced Feature Set-F1
- Super G3 FAX Board-AE2
- Super G3 2nd Line Fax Board-AE1
- Super G3 3rd/4th Line Fax Board-AE1
- Remote FAX Kit-A1
- Barcode Printing Kit-D1
- Web Access Software-H1
- USB Device Port-E1
- Multimedia Reader/Writer-A2
- Additional Memory Type D (512MB)
- 2.5inch/160GB HDD-G1
- 2.5inch/1TB HDD-H1
- Copy Control Interface Kit-A1
- iR-ADV Security Kit-C1 for IEEE 2600.1 Common Criteria Certification\*

\* Not available on top cassette.

\*\* Can be set to Cassette 2 only. Can not install Envelope Feeder Attachment and Tab Feeding Attachment at same time.

\*\*\* If "Quick Startup Settings for Main Power" is set to ON, it takes 7 seconds until the key operation on the touch panel display is available after turning on the main power.

† Includes consumables.

†† XPS cannot be printed directly from the Web Access software.

††† EPS can be printed directly only from Remote User Interface.

■ Not available at time of launch.

▲ The Inner 2-way Tray-F1, Inner Finisher-E1, Staple Finisher-J1, and Booklet Finisher-J1 cannot be installed at the same time.

NOTE: Some accessories require additional equipment or may be prerequisites for other options. Some accessories cannot be installed simultaneously. Check with your Canon Authorized Dealer for details.



1-800-OK-CANON  
www.usa.canon.com

Canon U.S.A., Inc.  
One Canon Plaza  
Lake Success, NY 11042

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGERUNNER, MEAP, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and hereby acknowledged. Specifications and availability subject to change without notice. Some items may not be available at this time. Please check for availability. All printer output images are simulated.

©2012 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

